

AW-HE20

Full-HD PTZ Camera with simultaneous 3G-SDI, HDMI & USB output



KEY FEATURES

- Compact size & wide angle
- Simultaneous 3G-SDI, HDMI & USB output
- High-Quality Video Streaming for More Comfortable Online Communication
- Excellent system flexibility to achieve smart wiring and smooth operation

Entry model suitable for use in small meeting rooms and small classrooms.

PTZ cameras play an increasingly important role in teleworking such as online meetings and online classes. The AW-HE20 offers high image quality, wide shooting angle and high-magnification zoom to provide more comfortable communication through high-quality video images and stable transmission. The AW-HE20 is compatible with a wide range of systems such as SDI, HDMI, USB and IP, thus allowing flexible camera setup and operation. The AW-HE20 is a high-quality entry model. The compact unit can be installed in a small place without getting in the way.

High-quality video streaming for more comfortable online communication

- Wide shooting range and high-magnification zoom deliver “the ambience of hall” intact.
- Auto Tracing software accurately follows and captures the speaker.

Excellent system flexibility to achieve smart wiring and smooth operation

- Easy installation/setup and compact system configuration.
- Single PC or controller can manage and control multiple cameras.
- Can be used as USB camera.
- Direct upload of videos to video livestreaming services.

Compact size and excellent functionality that do not disturb the existing video streaming environment

- Compact design blends in with the surroundings. Light weight and small size for added installation flexibility.
- Linkable with existing system.

SPECIFICATIONS

Power Requirements	DC12 V ± 10 % (10.8 V to 13.2 V) (Supplied AC adapter)
PoE+	IEEE802.3 at compliant
Current Consumption	TBD
Ambient Operating Temperature	0 °C to 40 °C (32°F to 104°F)
Ambient Operating Humidity	20 % to 90 % (no condensation)
Storage Temperature	-20°C to 50°C (-4 °F to 122 °F)
Mass	TBD
Dimensions (W x H x D)	TBD
Finish	AW-HE20W: White AW-HE20K: Black
Controller Supported	AW-RP150GJ, AW-RP60GJ, AW-RM50AG
Image Sensor	1/2.8-type MOS×1
Lens	Electric 12 x optical zoom F1.6 \varnothing F2.8 (f = 3.9 mm \varnothing 46.8 mm)
Zoom	Optical zoom: 12 x
Angle of View Range	horizontal angle of view: 71° (wide) to 6° (tele) Vertical angle of view: 43° (wide) to 3° (tele) Diagonal angle of view: 79° (wide) to 7° (tele)
Minimum Illumination	TBD
S/N	TBD
Horizontal Resolution	TBD
Output Format HDMI HD	1080/60p, 1080/59.94p, 1080/50p, 1080/60i, 1080/59.94i, 1080/50i, 1080/30p, 1080/29.97p, 1080/25p, 720/60p, 720/59.94p, 720/50p
Output Format SDI HD	1080/60p, 1080/59.94p, 1080/50p, 1080/60i, 1080/59.94i, 1080/50i, 1080/30p, 1080/29.97p, 1080/25p, 720/60p, 720/59.94p, 720/50p
Input	DC 12 V IN
Video Output	HDMI, 3G-SDI OUT
Input/Output Connector	LAN, RS-422, AUDIO IN, USB, RS-232C IN, RS-232C OUT
Installation Method	Stand-alone (Desktop) or suspended (Hanging)*2
Panning Range	±170°
Tilting Range	-30° \varnothing 90° *3
Quietness	NC40 or less
Supported operating systems and web browsers	*4
Windows	Windows 10 Windows® Internet Explorer® 11 \varnothing 32 bit / 64 bit \varnothing Microsoft Edge Google Chrome
Mac	Mac OS 10.15 Mac OS 10.14 Mac OS 10.13 Mac OS 10.12 Safari Google Chrome
Image Streaming Mode	JPEG(MJPEG), H.264, H.265
Image Resolution	1920×1080, 1280×720, 640×360
Note	*1 The main unit may appear in the video depending on the pan/tilt position. *2 To ensure safety, the unit must be secured using the mount bracket supplied. *3 The main unit may appear in the video depending on the pan/tilt position. *4 Supported OS indicated are for browsers current as of September 2021. See "Service and Support / PASS" for the latest information on browser support.

URL: <https://business.panasonic.co.uk/professional-camera/aw-he20>

CONTACT

Web: <https://business.panasonic.co.uk/professional-camera/contact-us>