

SOLID SHINE Series

3-Chip DLP™ Laser light source models
Lens not included with 3-Chip DLP™ models.

Large-Venue

	NEW PT-RQ50K	50,000 lm 51,000 lm (Center)	Native 4K			
	PT-RQ32K	26,000 lm 27,000 lm (Center)	4K+			
	PT-RZ31K	30,000 lm 31,000 lm (Center)	WUXGA			
	PT-RQ22K	20,000 lm 21,000 lm (Center)	4K+			
	PT-RZ21K	20,000 lm 21,000 lm (Center)	WUXGA			
	PT-RQ13K	10,000 lm	4K+			
	PT-RZ12K	12,000 lm	WUXGA			

1-Chip DLP™ Laser light source models

Installation

	NEW PT-RCQ10/L	10,000 lm 10,500 lm (Center)	2715 x 1697 dots ^{1,2}			
	PT-RCQ80/L	8,000 lm 8,400 lm (Center)	2715 x 1697 dots ^{1,2}			
	PT-RZ120/L	12,000 lm 12,600 lm (Center)	WUXGA			
	PT-RZ970/L	9,400 lm 10,000 lm (Center)	WUXGA			
	PT-RZ870/L	8,500 lm 8,800 lm (Center)	WUXGA			
	PT-RZ770/L	7,000 lm 7,200 lm (Center)	WUXGA			
	PT-RZ660/L	6,000 lm 6,200 lm (Center)	WUXGA			
	PT-RZ570 *	5,200 lm 5,400 lm (Center)	WUXGA			
	PT-RZ575 ⁴	5,000 lm 5,200 lm (Center)	WUXGA			Throw Ratio 0.8:1

*Featured image: PT-RZ570

LCD Laser light source models

Installation

	NEW PT-MZ16KL	16,000 lm	WUXGA				
	PT-MZ13KL	13,000 lm	WUXGA				
	PT-MZ10KL	10,000 lm	WUXGA				
	PT-MZ770/L	8,000 lm	WUXGA				
	PT-MW730/L	8,000 lm	WXGA				
	PT-MZ670/L	6,500 lm	WUXGA				
	PT-MZ570/L	5,500 lm	WUXGA				
	PT-MW630/L	6,500 lm	WXGA				
	PT-MW530/L	5,500 lm	WXGA				

Portable

LCD Laser light source models (Lens fixed)

	PT-VMZ60 *	6,000 lm	WUXGA				
	PT-VMZ50	5,000 lm	WUXGA				
	PT-VMZ40	4,500 lm	WUXGA				
	PT-VMW60	6,000 lm	WXGA				
	PT-VMW50	5,000 lm	WXGA				

LCD Lamp based models

Portable

	PT-VZ585N	5,000 lm	WUXGA				
	PT-VZ580	5,000 lm	WUXGA				
	PT-VW545N	5,500 lm	WXGA				
	PT-VW540	5,500 lm	WXGA				
	PT-VX615N	5,500 lm	XGA				
	PT-VX610	5,500 lm	XGA				
	PT-VZ470 ⁶	4,400 lm	WUXGA				
	PT-VW360	4,000 lm	WXGA				
	PT-VX430	4,500 lm	XGA				

LCD Lamp based models

Portable

Available from May 2020

	PT-LW376	3,600 lm	WXGA				
	PT-LW336	3,100 lm	WXGA				
	PT-LB426	4,100 lm	XGA				
	PT-LB386	3,800 lm	XGA				
	PT-LB356	3,300 lm	XGA				
	PT-LB306 ⁶	3,100 lm	XGA				

LCD Lamp based models

Short-Throw

Available from May 2020

	PT-TW381R	3,300 lm	WXGA				
	PT-TW380	3,300 lm	WXGA				
	PT-TX440 ⁶	3,800 lm	XGA				
	PT-TX350 ⁶	3,200 lm	XGA				

*Featured image: PT-TW381R



Mobile App -

The information of the Panasonic projectors and Professional displays from your iOS/Android devices.
panasonic.net/cns/prodisplays/support/mobile_app/

Space Player

1-Chip DLP™ Laser light source models

	PT-JX200	2,000 lm	XGA				
	PT-JW130	1,000 lm	WXGA				

LED

1-Chip DLP™ LED light source models (Lens fixed)

Available from July 2020

	PT-LRZ35	3,500 lm	WUXGA				
	PT-LRW35	3,500 lm	WXGA				

Lenses⁷⁾

Ultra-Short-Throw Lens

ET-D3LEU100

F value: 2.5 f=8.0 mm Zero Offset
0.397:1 [4K*]

Short-Throw Zoom Lens

ET-D3LEW200

F value: 2.5 f=13.8-18.1 mm Zero Offset
0.693-0.913:1 [4K*] Powered Zoom

Ultra-Short-Throw Zoom Lens

ET-DLE020

F value: 2.0 f=4.1-4.4 mm Zero Offset
0.280-0.299:1 [WUXGA] Powered Zoom

For 3-Chip DLP™ Projector¹⁰⁾
For 1-Chip DLP™ Projector

*1: Resolution 5120 x 3200 Pixels [Quad Pixel Drive: ON]. *2: With Smooth Pixel Drive: ON. *3: HDMI/DIGITAL LINK input only.
*4: With no lens shift lever. *5: To operate wireless projection, the optional Wireless Module ET-WM300 is required.
*6: The availability varies depending on the country. *7: To operate wireless projection, the optional Wireless Module AJ-WM50 is required. *8: To operate wireless projection, the optional Wireless Module ET-WM50 is required. *9: See our website for projector and lens compatibility. Projector may require the latest firmware update.
*10: ET-D3LEU100 is not compatible with PT-RQ50K. ET-D3LEW200 is not compatible with PT-RQ50K and RQ13K Series.
★ Available in black/white cabinet.
*S: The projector is able to emulate the same control commands of most previous Panasonic projectors when it is replacing.
Note: [L/L] Lens-less model. The specifications are subject to change without notice.
For more information, please visit the website >> panasonic.net/cns/projector/