



KX 08-A

HIGH-PERFORMANCE 2-WAY POINT-SOURCE ACTIVE SPEAKER



Description

The KX 08-A is a compact, high-output 2-way active speaker system engineered for professional users, combining precise directivity, high SPL capability, and advanced system integration. The low-frequency section features an 8" neodymium driver in a bass-reflex design; the high-frequency section comprises a neodymium compression driver with a 1.75" PKX dome, coupled to a 90° x 70° True Resistive Waveguide, rotatable by 90° to ensure flexible coverage options. An integrated two-channel 2000 W Class D amplifier with proprietary DSP processing and remote management via RDNet enables optimal system performance. Its weatherproof, multifunctional enclosure with Quick Fit and M10 inserts supports versatile deployment for ground-stacked, pole-mounted, or flown applications.

Features

- › 128 dB SPL Max
- › Rotatable 90° x 70° TRW horn
- › 8" neodymium woofer, 2.5" voice coil
- › 1,75" PKX dome, neodymium compression driver
- › Two-channel, 2000W Class-D amplifier
- › DSP Processing with FIRPHASE and BMC
- › RDNet Networked Management
- › powerCON TRUE1 TOP mains connectors

Part Number

13000900 KX 08-A

220-240 V

Black


EAN 8024530022808



KX 08-A

HIGH-PERFORMANCE 2-WAY POINT-SOURCE ACTIVE SPEAKER

Line Art 2D



TECHNICAL SPECIFICATIONS

Acoustical specifications

Frequency Response	65 Hz ÷ 20000 Hz
Max SPL @ 1m	128 dB
Horizontal coverage angle	90°
Vertical coverage angle	70°

Transducers

Compression Driver	1 x 1.0" neo, 1.75" v.c
Woofer	1 x 8" neo, 2.5" v.c

Input/Output section

Input signal	bal/unbal
Input connectors	XLR, RDNet Ethercon
Output connectors	XLR, RDNet Ethercon
Input sensitivity	-2 dBu/+4 dBu

Processor section

Crossover Frequencies	1400Hz
Protections	Thermal, HF
Limiter	Fast Limiter
Controls	Bypass, Linear/High Pass, Volume
RDNet	Onboard

Power section

Total Power	2000 W Peak
High frequencies	600 W Peak
Mid frequencies	1400 W Peak
Cooling	Convection
Connections	Powercon TRUE1 TOP IN/OUT

Standard compliance

Safety agency	CE compliant
---------------	--------------

Physical specifications

Cabinet/Case Material	Baltic birch plywood
Hardware	3X M10 TOP AND BOTTOM 2X PIN D.10 AND M10 SIDE
Handles	1 TOP
Pole mount/Cap	35 mm insert
Grille	Steel with clothing
Color	Black



KX 08-A

HIGH-PERFORMANCE 2-WAY POINT-SOURCE ACTIVE SPEAKER

Size / Weight	Height	450 mm / 17.72 inches	
	Width	260 mm / 10.24 inches	
	Depth	285.4 mm / 11.24 inches	
	Weight	11 kg / 24.25 lbs	
Rigging / Mounting	ACCESSORIES		
	FLOOR STANDS		
	13360109 AC PRO-FS	Black	EAN 8024530006471
	FLYING BRACKETS		
	13360031 AC EB 4X		EAN 8024530018870
	HORIZONTAL BRACKETS		
	13360714 HBR60714	Black	EAN 8024530023171
	POLE MOUNT KITS		
	13360232 AC PMX		EAN 8024530010058
	13360110 AC PRO-PM	Black	EAN 8024530006488
	13360067 PM-KIT M20	Black	EAN 8024530014599
	VERTICAL BRACKETS		
	13360715 VBR60715	Black	EAN 8024530023188
	Protections	COVERS	
13360713 CVR60713		Black	EAN 8024530023164
RAIN PROTECTIONS			
Cables	13360689 RPR60689	Black	EAN 8024530022914
	CABLES KIT		
	13360102 AC XLR 3M3F		EAN 8024530006402