



# KXM 25-A

ACTIVE HIGH PERFORMANCE COAXIAL STAGE MONITOR



## Description

The KXM 25-A is a very high-output active monitor designed for maximum impact, precision, and controlled coverage in professional environments. Reaching 137 dB SPL Max and powered by a 3200 W peak Class-D amplifier, it delivers a focused 60° x 60° constant-directivity pattern that supports a clean monitoring window and strong gain-before-feedback. Its coaxial architecture combines a 15" neodymium coaxial woofer with a 3.5" voice coil and a 2.5" neodymium coaxial compression driver, keeping the sound coherent and consistent as performers move. Integrated DSP processing with FIRPHASE and BMC improves coherence and definition in real-world conditions, and onboard RDNet control enables centralized monitoring and control for efficient stage workflows. The multifunctional cabinet makes KXM 25-A equally effective as a stage wedge or as a controlled point source in portable FOH or fill applications.

## Features

- › 137 dB SPL Max
- › 3200 W peak power Class D Amplifier
- › 60 x 60 constant directivity coverage
- › 15" neo coaxial woofer, 3.5" voice coil
- › 2.5" neo coaxial compression driver
- › FIRPHASE and Bass Motion Control
- › RDNet Networked Management
- › Multifunctional cabinet with coaxial transducers' design

## Part Number


13000978	KXM 25-A	EU	220-240 V	Black	EAN 8024530025038
13000979	KXM 25-A	US	100-120 V	Black	EAN 8024530025052



# KXM 25-A

ACTIVE HIGH PERFORMANCE COAXIAL STAGE MONITOR

Line Art 2D



## TECHNICAL SPECIFICATIONS

<b>Acoustical specifications</b>	Frequency Response	50 Hz - 20000 Hz
	Max SPL @ 1m	133 dB
	Horizontal coverage angle	60°
	Vertical coverage angle	60°
<b>Transducers</b>	Compression Driver	Coaxial 1.5" neo, 2.5" v.c
	Woofer	Coaxial 15" neo, 3.5" v.c
<b>Input/Output section</b>	Input signal	bal/unbal
	Input connectors	XLR, RDNet Ethercon
	Output connectors	XLR, RDNet Ethercon
	Input sensitivity	-2 dBu/+4 dBu
<b>Processor section</b>	Crossover Frequencies	900 Hz
	Protections	Thermal, HF
	Limiter	Soft Limiter
	Controls	Proces., 8 sel. presets
<b>Power section</b>	RDNet	Onboard
	Total Power	3200 W Peak
	High frequencies	1200 W Peak
	Low frequencies	2000 W Peak
<b>Standard compliance</b>	Cooling	Convection
	Connections	Powercon TRUE1 TOP IN/OUT
	Safety agency	CE compliant



# KXM 25-A

## ACTIVE HIGH PERFORMANCE COAXIAL STAGE MONITOR

Physical specifications	Cabinet/Case Material	Baltic birch plywood			
	Handles	1 Top			
	Pole mount/Cap	35 mm insert			
	Grille	Steel			
	Color	Black			
	Size / Weight	Height	353 mm / 13.9 inches		
		Width	580 mm / 22.83 inches		
Depth		486 mm / 19.13 inches			
Weight		18 kg / 39.68 lbs			
Rigging / Mounting	<b>ACCESSORIES</b>				
	<b>FLOOR STANDS</b>				
	13360109	AC PRO-FS	Black	EAN 8024530006471	
	<b>POLE MOUNT KITS</b>				
	13360232	AC PMX		EAN 8024530010058	
	13360110	AC PRO-PM	Black	EAN 8024530006488	
	13360067	PM-KIT M20	Black	EAN 8024530014599	
	Protections	<b>COVERS</b>			
		13360766	CVR60766	Black	
	Cables	<b>RAIN PROTECTIONS</b>			
		13360651	RPR60651	Black	EAN 8024530025069
		<b>CABLES</b>			
		12399019	CBL ETHERCON TO XLR F 0.2M	Black	EAN 8024530013882
		12399020	CBL ETHERCON TO XLR M 0.2M	Black	EAN 8024530013899
		<b>CABLES KIT</b>			
		13360102	AC XLR 3M3F		EAN 8024530006402
		12399016	CBL ETHERCON 0.7M	Black	EAN 8024530013844
		12399017	CBL ETHERCON 1.5M	Black	EAN 8024530013851
		12399035	CBL ETHERCON 3M	Black	EAN 8024530013868
	12399018	CBL ETHERCON 5M	Black	EAN 8024530013875	